

# UHPC 20A Channel Module



## UHPC Channel Modules - The Best in Precision

NOVONIX's industry leading Ultra-High Precision Coulometry (UHPC) Channel Modules accurately measure and control current and voltage, with high precision and low noise, providing better quality data that allow for greater confidence.

Part Number:  
**CMA-HFX-99-56**



## Measurement

### Current

**Resolution:** <20ppm  
**Accuracy:** 0.005% FSR  
**Noise:** 0.002% FSR  
**Temperature Coefficient:** 0.002% FSR over 23 ±5°C

### Voltage

**Resolution:** 1µV  
**Accuracy:** 200µV  
**Noise:** 100µV  
**Temperature Coefficient:** 0.002% FSR over 23 ±5°C

## Source

### Current

**Range:** 2A, 20A  
**Resolution:** <20ppm FSR  
**Accuracy:** 0.01% FSR  
**Noise:** 0.002% FSR  
**Temperature Coefficient:** 0.002% FSR over 23 ±5°C

### Voltage

**Range:** 0V-5V  
**Resolution:** <50µV  
**Accuracy:** 200µV  
**Noise:** 100µV  
**Temperature Coefficient:** 0.002% FSR over 23 ±5°C

## Timing

**Resolution:** 10ms  
**Measurement Frequency:** 6Hz  
**Accuracy:** 2ppm

## Integrated RTD Temperature Sensing

**Resolution:** ±0.01°C  
**Accuracy:** ±0.5°C  
**Noise:** ±0.05°C

## Technical Considerations\*

**Dimensions WxHxD (In):** 19" x 3.5" x 28"  
**Rack Space (U):** 2U  
**Weight (lbs):** 34  
**Number of Test Channels:** 4  
**Bench and Rack Mountable?:** Yes

**Power Draw (VA):** 1500VA  
**Voltage:** Voltages Supplied by Power Module  
**Minimum Discharge Voltage:** 0.005V  
**Required Lab Temperature Range:** 18°C - 28°C  
**Required Lab Temperature Stability:** ±1°C

*For best performance, we recommend pairing Channel Modules with NOVONIX Thermal Chambers, which are specifically designed to provide the temperature stability required for UHPC experiments.*

**NOVONIX**<sup>®</sup>

[novonixgroup.com](http://novonixgroup.com)

Contact us to learn how UHPC technologies can improve your battery development, manufacturing, selection and more: [bts-sales@novonixgroup.com](mailto:bts-sales@novonixgroup.com)